

Description

Cast premium PVC film with high visibility at all daylight conditions, developed especially for emergency vehicles. Particularly effective in twilight and in conditions of low visibility. The ORACAL® 7710RA Fluorescent Premium Cast Plus series is available in the following colours: 029: fluorescent yellow and 039: fluorescent red. The *RapidAir*® technology enables easy and quick bubble-free application, especially of large-sized graphics. Entrapped air can be easily removed by simply smoothing it out under the film. The special adhesive enables adhesion onto lacquered surfaces, as well as onto uneven and corrugated surfaces. The product should be worked in, cut and applied with an overlap at the edge, for more curved surfaces, or for corrugations and rivets. The applied material is easy to remove with the appropriate equipment.

Release Paper

Double sided PE coated *RapidAir*® paper, one side siliconized, 143 g/m²

Adhesive

Solvent polyacrylate, repositionable, with permanent final adhesion

Area of use

For outdoor use for the production of high-quality adhesive bonds on vehicles and means of transport, which are to attract a special attention.

Technical Data

Thickness ⁽¹⁾ (without protective paper and adhesive)	170 micron
Dimensional stability ⁽¹⁾ (FINAT TM 14)	Adhered to steel, shrinkage 0,15 mm max.
Temperature resistance ⁽²⁾	Adhered to aluminium, -50° C to +120° C, no variation
Sea water resistance (DIN EN ISO 9227)	Adhered to aluminium, after 100h/35° C, no variation
Resistance to solvents and chemicals	At room temperature, 72h after adhesion to aluminium, short-term resistance to most oils and greases, fuels, aliphatic solvents, weak acids, salts and alkalis
Adhesive power ⁽¹⁾ (FINAT TM 1, after 24h, stainless steel)	16 N/25 mm
Tensile strength ⁽¹⁾ (DIN EN ISO 527)	Along: > 18 MPa Across: > 18 MPa
Elongation at break ⁽¹⁾ (DIN EN ISO 527)	Along: > 150% Across: > 150%
Shelf life ⁽³⁾	2 years
Application temperature	> +15° C
Maximum service life by specialist application and proper care and usage applies for vertical outdoor exposure. ⁽⁴⁾	Fluorescent red: 3 years Fluorescent yellow: 3 years

⁽¹⁾ average ⁽²⁾ short-time exposure ⁽³⁾ in original packaging, at 20° C and 50% relative humidity ⁽⁴⁾ normal climate of Central Europe. The real and expected durability depends mainly on the environmental conditions, but also on the pre-treatment of the substrate and the regular care. Please follow the additional notes at the end of this datasheet. Further information is available here:

www.orafol.com/gp/europe/en/support

Note

Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. Furthermore, the application information published by ORAFOL must be considered. The batch traceability according to ISO 9001 is possible on the basis of the roll number.

IMPORTANT NOTICE

All ORACAL® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORACAL® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORACAL® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice. ORACAL® is a registered trademark of ORAFOL Europe GmbH.