

**Typhoon E Warm series** is entry level Full-auto roll to roll warm assist model with ABS tooling side cover construction; The accurate CNC metal cutting program secure align laminating and quality finishing; Ideal for wide format laminating or mounting application use.

**Features:**

- One side hand crank lift up system
- Drop in type interchangeable 3" aluminum shaft
- Membrane control panel
- Variable speed control
- Forward and reverse direction control
- E-stop and photocell installed for safety
- Both auto and foot pedal switch mode
- Removable pressure plate
- Stand assembled at customer site
- CE certified



**Model: BU-1400 / 1600 / 1700 E Warm**

Reliable Finishing Solution Manufacturer

	BU-1400E Warm	BU-1600E Warm	BU-1700E Warm
Max. Working Width	1400mm(55")	1600mm(63")	1700mm(67")
Variable Working Speed	0-6m/min	0-6m/min	0-6m/min
Max. Nip Opening	35mm(1.38in)	35mm(1.38in)	35mm(1.38in)
Max. Heat Assist temp	60°C	60°C	60°C
Roller Diameter	120mm	120mm	120mm
Top Roller Material	Silicone rubber	Silicone rubber	Silicone rubber
Bottom Roller Material	Natural rubber	Natural rubber	Natural rubber
Drive Motor	AC110V, 230V/90W	AC110V, 230V/90W	AC110V, 230V/90W
Power Consumption	1300W	1300W	1300W
Power Requirement	AC110V/50-60Hz AC230V/50-60Hz	AC110V/50-60Hz AC230V/50-60Hz	AC110V/50-60Hz AC230V/50-60Hz
Machine Size	1800*600*1300mm	2000*600*1300mm	2100*600*1300mm
Shipping Dimensions	1950*710*750mm	2150*710*750mm	2450*710*750mm
Weight ( NW / GW)	220Kg / 260Kg	230Kg / 270Kg	240Kg / 280Kg